(TILE DOCTOR) DUOCLEAN

Page: 1

Compilation date: 29/03/2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: (TILE DOCTOR) DUOCLEAN

Product code: HC0028

Synonyms: HC0028 / TD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: FOR PROFESSIONAL AND INDUSTRIAL USE ONLY. Water based hard surface cleaner.

1.3. Details of the supplier of the safety data sheet

Company name: TILE DOCTOR

The Old Smithy 50F Market Street Carnforth Lancashire LA5 9LB United Kingdom Tel: 0845 652 4652 Email: info@tiledoctor.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Eye Irrit. 2: H319; Aquatic Acute 1: H400; -: EUH031

Most important adverse effects: Contact with acids liberates toxic gas. Causes skin irritation. Causes serious eye irritation. Very toxic to aquatic life.

2.2. Label elements

Label elements:

Hazard statements: EUH031: Contact with acids liberates toxic gas.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental



(TILE DOCTOR) DUOCLEAN

Signal words:	Warning
-	5
Precautionary statements:	P102: Keep out of reach of children.
	P260: Do not breathe spray.
	P262: Do not get in eyes, on skin, or on clothing.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P302+352: IF ON SKIN: Wash with plenty of water/soap.
	P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
	P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
2.3. Other hazards	

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM HYPOCHLORITE SOLUTION CL ACTIVE - REACH registered number(s): 01-2119488154-34-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
231-668-3	7681-52-9	-	Skin Corr. 1B: H314; Aquatic Acute 1:	1-10%
			H400; -: EUH031	

SODIUM CARBONATE - REACH registered number(s): 01-2119485498-19-XXXX

207-838-8	497-19-8	-	Eye Irrit. 2: H319	1-10%
-----------	----------	---	--------------------	-------

Non-classified ingredients:

SODIUM BICARBONATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
205-633-8	144-55-8	-	-	1-10%

PRIMARY ALCOHOL ETHOXYLATE CD916

- 68439-45-2 - Acute Tox. 4: H302; Eye Dam. 1: H318 <1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

Page: 2

(TILE DOCTOR) DUOCLEAN

		Page:	3
4.2. Most important symptoms	and effects, both acute and delayed		
Skin contact:	There may be irritation and redness at the site of contact.		
Eye contact:	There may be irritation and redness. The eyes may water profusely.		
Ingestion:	There may be soreness and redness of the mouth and throat.		
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may		
	cause coughing or wheezing.		
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.		_
4.3. Indication of any immediat	e medical attention and special treatment needed		
Immediate / special treatment:	Eye bathing equipment should be available on the premises.		
Section 5: Fire-fighting measu	res		
5.1. Extinguishing media			
Extinguishing media:	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool	I	
	containers.		
5.2. Special hazards arising fro	om the substance or mixture		
Exposure hazards:	In combustion emits toxic fumes. Water based product. Advice relates to dry residues after		
	water has evaporated.		
5.3. Advice for fire-fighters			
Advice for fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with		
	skin and eyes.		
Section 6: Accidental release r	·		
6.1. Personal precautions, prot	tective equipment and emergency procedures		
Personal precautions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from		
	downwind. If outside keep bystanders upwind and away from danger point. Mark out the		
	contaminated area with signs and prevent access to unauthorised personnel. Turn leaking		
	containers leak-side up to prevent the escape of liquid.		
6.2. Environmental precautions	3		
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.		
6.3. Methods and material for c	containment and cleaning up		
Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal		
	by an appropriate method. Wash the spillage site with large amounts of water.		
6.4. Reference to other section	IS		
Reference to other sections:	Refer to section 8 of SDS.		
Section 7: Handling and storage	ge		

(TILE DOCTOR) DUOCLEAN

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. The floor of the storage room must be
	impermeable to prevent the escape of liquids.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Protective gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid	
Colour:	Colourless	
Odour:	Characteristic odour	
Evaporation rate:	Slow	
Solubility in water:	Highly soluble	
Viscosity:	Non-viscous	
Boiling point/range°C:	100Melting point/range°C:	0
Flammability limits %: lower:	Not applicable. upper:	Not applicable.
Flash point°C:	Not applicable. Part.coeff. n-octanol/water:	Not applicable.
Autoflammability°C:	Not applicable. Vapour pressure:	Not applicable.
Relative density:	1.080 pH :	9 - 10
VOC g/l:	Not applicable.	

(TILE DOCTOR) DUOCLEAN

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong acids. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of hydrogen chloride / phosgene.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM HYPOCHLORITE SOLUTION...100% CL ACTIVE

ORL MUS LD50 5800 mg/kg	
---	--

SODIUM CARBONATE

ORL	MUS	LD50	6600	mg/kg
ORL	RAT	LD50	4090	mg/kg
SCU	MUS	LD50	2210	mg/kg

SODIUM BICARBONATE

ORL RBT LD50 4220 mg/Kg	
---	--

PRIMARY ALCOHOL ETHOXYLATE CD916

IHL F	RAT LC5	50 >5	mg/l
-------	---------	-------	------

(TILE DOCTOR) DUOCLEAN

Page: 6

ORL	RAT	LD50	200-2000	mg/kg
SKN	RAT	LD50	>2000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SODIUM BICARBONATE

FATHEAD MINNOWS 96H LC50	8600	g/l
--------------------------	------	-----

PRIMARY ALCOHOL ETHOXYLATE CD916

FISH	96H LC50	1-10	mg/l	
------	----------	------	------	--

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable. The surfactant(s) contained in this preparation complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Volatile. Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

(TILE DOCTOR) DUOCLEAN

Page: 7

Section 13: Disposal considerations

 13.1. Waste treatment methods

 Disposal operations:

 Transfer to a suitable container and arrange for collection by specialised disposal company.

 Recovery operations:

 Not applicable.

Waste code number: 20 01 30

Disposal of packaging: Dispose of as normal industrial waste. Clean with water.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Marine pollutant: No

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Detergent Regulations EC648/2004, the product contains amongst other ingredients:-

(TILE DOCTOR) DUOCLEAN

Non-Ionic surfactants <5% Chlorine based bleaching agents <5% IMPORTANT NOTE: Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels in the mixed product. See sections 2 and 3 for the calculated hazard and risk phrases for the blended product. Phrases used in s.2 and s.3: EUH031: Contact with acids liberates toxic gas. H302: Harmful if swallowed. H314: Causes severe skin burns and eye damage. H315: Causes skin irritation. H318: Causes serious eye damage. H319: Causes serious eye irritation. H400: Very toxic to aquatic life. Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. For professional and industrial use only.

Page: 8